


PRODUCT PHOTOGRAPH



TECHNICAL DRAWING



COMPATIBLE WITH

- On/Off Driver: N/A
- Triac Driver: N/A
- Dali Driver: N/A

GENERAL INFORMATION

|                         |                          |
|-------------------------|--------------------------|
| Product Code            | 8254429                  |
| Product Category        | Linear                   |
| Product Family          | Linear Lighting Profiles |
| Mounting Location       | Ceiling                  |
| Application Environment | Indoor                   |

DIMENSION & WEIGHT

|              |                    |
|--------------|--------------------|
| LxWxH (cm)   | L: 120 W: 3,8 H: 7 |
| Cut out (cm) | 0                  |
| Weight (Kgr) | 2.85               |

MATERIAL & COLOR

|                |           |
|----------------|-----------|
| Product Color  | White     |
| Body Material  | Aluminium |
| Cover Material | PMMA      |

APPLICATION & MOUNTING

|                            |         |
|----------------------------|---------|
| Ambient Working Temp.      | 45 C    |
| Type of Protection         | IP20    |
| Protection Class IK        | IK04    |
| Dimmable                   | NO      |
| Type of Dimming (Optional) | N/A     |
| Mounting type              | Surface |
| Mounting Depth (cm)        | Ceiling |
| Led Module Replaceable     | N/A     |
| Light Source               | N/A     |
| Adjustable                 | No      |



# NOVA LUCE

## PRODUCT DATASHEET

Version: 001

### ELECTRICAL DATA

|                         |            |
|-------------------------|------------|
| Power (Nominal)         | 40 W       |
| Input voltage (Nominal) | 220-240Vac |
| Mains Frequency         | 50/60Hz    |
| Output voltage          | N/A        |
| Output Current          | N/A        |
| Power Factor            | N/A        |
| Efficiency              | N/A        |
| SVM                     | N/A        |
| Pst                     | N/A        |
| Class                   | I          |

### PHOTOMETRICAL DATA

|                           |            |
|---------------------------|------------|
| Luminus Flux              | 2480 lm    |
| Luminous Efficacy         | 62 lm/W    |
| Color Temperature         | 3000 K     |
| Light Color (Designation) | Warm White |
| CRI                       | >80        |
| SDCM                      | <6         |
| Beam Angle                | 120        |
| UGR                       | N/A        |

### LIFESPAN

|          |             |
|----------|-------------|
| Lifetime | 50000 hours |
|----------|-------------|

### CERTIFICATES

|              |          |
|--------------|----------|
| Certificates | CE, UKCA |
|--------------|----------|

### WARRANTY

|          |         |
|----------|---------|
| Warranty | 5 years |
|----------|---------|

### LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com

