

NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A

Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE

Model identifier: 8502962

Type of light source: G9 (BULB EXCLUDED)



Product information Sheet

General Information

Material number	8502962
Type	Pendant lamp
Product segment	INDOOR

Dimensions

Diameter (in cm)	46Cm
Height (in cm)	140Cm
Net Weight (in cm)	8.2 Kg

Material & Colour

Enclosure Material	Aluminium & Crystal
Colour	Matt white
Adjustable	

Functionality

Switch Type	
Function	
Battery	No
USB Charger	No

Technical Information

Protection Degree	IP20
Protection Class	
Mains Voltage	230V
max. Wattage	6xG9
Lumen	
Equivalence With Incandescent Lamp (W)	
Colour Temperature	
Nominal Lifetime (in h)	
Switching Cycles	
Colour Rendering Index (Ra, CRI)	
Rated Lamp Power (0,1W precision)	
Colour Tolerance (LED, SDCM)	

Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	-
Non-directional or directional [NDLS/DLS]	-
Mains or non-mains [MLS/NMLS]	-
Connected light source (CLS) [yes/no]	
Colour-tuneable light source [yes/no]	
Envelope [no/second/non-clear]	
High luminance light source [yes/no]	
Anti-glare shield [yes/no]	
Dimmable [yes/only with specific dimmers/no]	

General Product parameters

Energy consumption in on-mode (kWh/1000h)

Energy efficiency class

The calculations performed with the parameters, including the determination of the energy class

Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)

Correlated colour temperature, rounded to the nearest 100 K,
or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :

On-mode power (P_{on}), expressed in W [x,x]

Standby power (P_{sb}), expressed in W and rounded to the second decimal

Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal

Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set

Outer dimensions without separate control gear, lighting control parts
and non-lighting control parts, if any (millimetre):

Spectral power distribution in the range 250 nm to 800 nm, at full-load

Claim of equivalent power (c)

If yes, equivalent power (W)

Chromaticity coordinates (x and y)

Parameters for directional light sources

Peak luminous intensity (cd)

Beam angle in degrees, or the range of beam angles that can be set

Standby Power (P_{sb}) in W

Beam Angle in degrees for directional light source

Parameters for LED and OLED light sources

R9 colour rendering index value

Survival factor [x,xx]

The lumen maintenance factor [x,xx]

Displacement factor ($\cos \phi_1$)

Colour consistency in MacAdam ellipses

Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage

If yes then replacement claim (W)

Flicker metric ($P_{\text{st Lm}}$) [x,x]

Stroboscopic effect metric (SVM) [X,X]

Displacement factor ($\cos \phi_1$) for LED and OLED mains light sources LED/OLED

Colour consistency in MacAdam ellipse steps for LED and OLED light sources

Flicker metric ($P_{\text{st LM}}$) for LED and OLED light sources

Stroboscopic effect metric (SVM) for LED and OLED light sources

P_{on} in W

