

NOVA LUCE

PRODUCT DATASHEET

Version: 001

PRODUCT PHOTOGRAPH




GENERAL INFORMATION

Product Code	9009060
Product Category	Systems
Product Family	Uprail
Mounting Location	Ceiling
Application Environment	Indoor

DIMENSION & WEIGHT

LxWxH (cm)	L:33 W:2.1 H:7 cm
Cut out (cm)	N/A
Weight (Kgr)	N/A

TECHNICAL DRAWING



MATERIAL & COLOR

Product Color	Black
Body Material	Aluminium
Cover Material	N/A

APPLICATION & MOUNTING

Ambient Working Temp.	45 C
Type of Protection	IP20
Protection Class IK	IK04
Dimmable	Yes
Type of Dimming (Optional)	Triac
Mounting type	Track
Mounting Depth (cm)	Ceiling
Led Module Replaceable	No
Light Source	Led
Adjustable	No

COMPATIBLE WITH

— On/Off Driver: N/A

— Triac Driver: N/A

— Dali Driver: N/A

NOVA LUCE S.A

Schimatari Viotias
32009, Greece

+30 22620 58 121
+30 22620 56 743

info@novaluce.com
www.novaluce.com



NOVA LUCE

PRODUCT DATASHEET

Version: 001

ELECTRICAL DATA

Power (Nominal)	10
Input voltage (Nominal)	24Vdc
Mains Frequency	50/60Hz
Output voltage	N/A
Output Current	N/A
Power Factor	N/A
Efficiency	N/A
SVM	N/A
Pst	N/A
Class	III

PHOTOMETRICAL DATA

Luminus Flux	374
Luminous Efficacy	37.4
Color Temperature	3000
Light Color (Designation)	Warm White
CRI	>90
SDCM	<3
Beam Angle	24
UGR	<10

LIFESPAN

Lifetime	50000
----------	-------

CERTIFICATES

Certificates	CE, UKCA
--------------	----------

WARRANTY

Warranty	5 Years
----------	---------

LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias
32009, Greece

+30 22620 58 121
+30 22620 56 743

info@novaluce.com
www.novaluce.com

