

NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A

Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE

Model identifier: 9018502

Type of light source: LED



Product information Sheet

General Information

Material number	9018502
Type	Wall Lamp
Product segment	INDOOR

Dimensions

Length (in cm)	14 Cm
Width (in cm)	7.5 Cm
Height (in cm)	20 Cm
Height 2 (in cm)	
Cut Out (in cm)	
Net Weight (in cm)	0.88Kg

Material & Colour

Enclosure Material	Aluminium & Glass
Colour	Sandy Black
Adjustable	

Functionality

Switch Type	Button switch
Function	-
Battery	No
USB Charger	No

Technical Information


Protection Degree	IP54
Protection Class	II
Mains Voltage	220-240V
max. Wattage	5W+1x3W
Lumen	400Lm + 150Lm
Equivalence With Incandescent Lamp (W)	
Colour Temperature	3000K
Nominal Lifetime (in h)	25000H
Switching Cycles	12000
Colour Rendering Index (Ra, CRI)	83,3
Rated Lamp Power (0,1W precision)	
Colour Tolerance (LED, SDCM)	<6

Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	DLS
Mains or non-mains [MLS/NMLS]	MLS
Connected light source (CLS) [yes/no]	No
Colour-tuneable light source [yes/no]	No
Envelope [no/second/non-clear]	No
High luminance light source [yes/no]	No
Anti-glare shield [yes/no]	No
Dimmable [yes/only with specific dimmers/no]	No

General Product parameters

Energy consumption in on-mode (kWh/1000h)	
Energy efficiency class	G
The calculations performed with the parameters, including the determination of the energy class	96,12
Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	653,87lm
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :	3000K
On-mode power (P_{on}), expressed in W [x,x]	8W
Standby power (P_{sb}), expressed in W and rounded to the second decimal	0
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	N/A
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set	CRI>80
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):	
Spectral power distribution in the range 250 nm to 800 nm, at full-load	



Claim of equivalent power (c)	Yes
If yes, equivalent power (W)	60W
Chromaticity coordinates (x and y)	x=0.4413 y=0.4042

Parameters for directional light sources

Peak luminous intensity (cd)	
Beam angle in degrees, or the range of beam angles that can be set	40°
Stanby Power (P_{sb}) in W	0
Beam Angle in degrees for directional light source	60

Parameters for LED and OLED light sources

R9 colour rendering index value	10
Survival factor [x,xx]	>90%
The lumen maintenance factor [x,xx]	95,58%
Displacement factor ($\cos \phi_1$)	≥0.5
Colour consistency in McAdam ellipses	<6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage	No
If yes then replacement claim (W)	
Flicker metric ($P_{st} Lm$) [x,x]	≤ 1.0
Stroboscopic effect metric (SVM) [X,X]	≤ 0.4
Displacement factor ($\cos \phi_1$) for LED and OLED mains light sources LED/OLED	≥0.5
Colour consistency in MacAdam ellipse steps for LED and OLED light sources	<6
Flicker metric ($P_{st} LM$) for LED and OLED light sources	≤ 1.0
Stroboscopic effect metric (SVM) for LED and OLED light sources	≤ 0.4
P_{on} in W	8W

