


PRODUCT PHOTOGRAPH



TECHNICAL DRAWING



COMPATIBLE WITH

- On/Off Driver: 9020170
- Triac Driver: N/A
- Dali Driver: 9844145(Remote)

GENERAL INFORMATION

Product Code	9030692
Product Category	Downlights
Product Family	Loggia
Mounting Location	Ceiling
Application Environment	Indoor

DIMENSION & WEIGHT

LxWxH (cm)	D:3 H:2.2
Cut out (cm)	2,5
Weight (Kgr)	N/A

MATERIAL & COLOR

Product Color	White
Body Material	Aluminium
Cover Material	N/A

APPLICATION & MOUNTING

Ambient Working Temp.	45 C
Type of Protection	IP44
Protection Class IK	IK03
Dimmable	No
Type of Dimming (Optional)	N/A
Mounting type	Recessed
Mounting Depth (cm)	Ceiling
Led Module Replaceable	No
Light Source	Led
Adjustable	No



NOVA LUCE

PRODUCT DATASHEET

Version: 001

ELECTRICAL DATA

Power (Nominal)	1
Input voltage (Nominal)	3Vdc
Mains Frequency	50/60Hz
Output voltage	3Vdc
Output Current	350mA
Power Factor	0,5
Efficiency	>68%
SVM	<0.4
Pst	<1
Class	III

PHOTOMETRICAL DATA

Luminus Flux	98
Luminous Efficacy	98
Color Temperature	3000
Light Color (Designation)	Warm White
CRI	>90
SDCM	<3
Beam Angle	23
UGR	<7

LIFESPAN

Lifetime	50000
----------	--------------

CERTIFICATES

Certificates	CE, UKCA
--------------	-----------------

WARRANTY

Warranty	5 Years
----------	----------------

LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias
32009, Greece

+30 22620 58 121
+30 22620 56 743

info@novaluce.com
www.novaluce.com

