

### PRODUCT PHOTOGRAPH




### GENERAL INFORMATION

|                         |            |
|-------------------------|------------|
| Product Code            | 9031786    |
| Product Category        | Downlights |
| Product Family          | Delve      |
| Mounting Location       | Ceiling    |
| Application Environment | Outdoor    |

### DIMENSION & WEIGHT

|              |           |
|--------------|-----------|
| LxWxH (cm)   | D:4 H:6.4 |
| Cut out (cm) | 3,5       |
| Weight (Kgr) | N/A       |

### TECHNICAL DRAWING



### MATERIAL & COLOR

|                |           |
|----------------|-----------|
| Product Color  | Black     |
| Body Material  | Aluminium |
| Cover Material | N/A       |

### APPLICATION & MOUNTING

|                            |            |
|----------------------------|------------|
| Ambient Working Temp.      | 45 C       |
| Type of Protection         | IP65       |
| Protection Class IK        | IK05       |
| Dimmable                   | Yes        |
| Type of Dimming (Optional) | Triac/Dali |
| Mounting type              | Recessed   |
| Mounting Depth (cm)        | Ceiling    |
| Led Module Replaceable     | No         |
| Light Source               | Led        |
| Adjustable                 | No         |

### COMPATIBLE WITH

— On/Off Driver: 9030471

— Triac Driver: 9844008(Remote)

— Dali Driver: 9844146



# NOVA LUCE

## PRODUCT DATASHEET

Version: 001

### ELECTRICAL DATA

|                         |         |
|-------------------------|---------|
| Power (Nominal)         | 5       |
| Input voltage (Nominal) | 18Vdc   |
| Mains Frequency         | 50/60Hz |
| Output voltage          | 18Vdc   |
| Output Current          | 250mA   |
| Power Factor            | 0,55    |
| Efficiency              | >83%    |
| SVM                     | <0.4    |
| Pst                     | <1      |
| Class                   | III     |

### PHOTOMETRICAL DATA

|                           |            |
|---------------------------|------------|
| Luminus Flux              | 199        |
| Luminous Efficacy         | 39.8       |
| Color Temperature         | 2700       |
| Light Color (Designation) | Warm White |
| CRI                       | 97         |
| SDCM                      | <3         |
| Beam Angle                | 36         |
| UGR                       | <12        |

### LIFESPAN

|          |       |
|----------|-------|
| Lifetime | 50000 |
|----------|-------|

### CERTIFICATES

|              |          |
|--------------|----------|
| Certificates | CE, UKCA |
|--------------|----------|

### WARRANTY

|          |         |
|----------|---------|
| Warranty | 5 Years |
|----------|---------|

### LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com

