

NOVA LUCE


PRODUCT DATASHEET

Version: 001

PRODUCT PHOTOGRAPH



TECHNICAL DRAWING



COMPATIBLE WITH

- On/Off Driver: Included
- Triac Driver: 9844008(Remote)
- Dali Driver: 9621523

GENERAL INFORMATION

Product Code	9040100
Product Category	Downlights
Product Family	Cone
Mounting Location	Ceiling
Application Environment	Indoor

DIMENSION & WEIGHT

LxWxH (cm)	D:3.8 H:7.5
Cut out (cm)	3,5
Weight (Kgr)	N/A

MATERIAL & COLOR

Product Color	White
Body Material	Aluminium
Cover Material	N/A

APPLICATION & MOUNTING

Ambient Working Temp.	45 C
Type of Protection	IP20
Protection Class IK	IK03
Dimmable	Yes
Type of Dimming (Optional)	Triac/Dali
Mounting type	Recessed
Mounting Depth (cm)	Ceiling
Led Module Replaceable	No
Light Source	Led
Adjustable	No

NOVA LUCE S.A

Schimatari Viotias
32009, Greece

+30 22620 58 121
+30 22620 56 743

info@novaluce.com
www.novaluce.com



NOVA LUCE

PRODUCT DATASHEET

Version: 001

ELECTRICAL DATA

Power (Nominal)	8
Input voltage (Nominal)	220-240Vac
Mains Frequency	50/60Hz
Output voltage	36Vdc
Output Current	180
Power Factor	0,5
Efficiency	>78.5%
SVM	<0.4
Pst	<1
Class	II

PHOTOMETRICAL DATA

Luminus Flux	560
Luminous Efficacy	70
Color Temperature	3000
Light Color (Designation)	Warm White
CRI	>90
SDCM	<3
Beam Angle	38
UGR	<12

LIFESPAN

Lifetime	50000
----------	--------------

CERTIFICATES

Certificates	CE, UKCA
--------------	-----------------

WARRANTY

Warranty	5 Years
----------	----------------

LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias
32009, Greece

+30 22620 58 121
+30 22620 56 743

info@novaluce.com
www.novaluce.com

