

# NOVA LUCE


## PRODUCT DATASHEET

Version: 001

### PRODUCT PHOTOGRAPH



### TECHNICAL DRAWING



### COMPATIBLE WITH

— On/Off Driver: Included

— Triac Driver: N/A

— Dali Driver: N/A

### GENERAL INFORMATION

|                         |            |
|-------------------------|------------|
| Product Code            | 9050803    |
| Product Category        | Downlights |
| Product Family          | Hermit     |
| Mounting Location       | Ceiling    |
| Application Environment | Indoor     |

### DIMENSION & WEIGHT

|              |               |
|--------------|---------------|
| LxWxH (cm)   | D:22.2 H:2.58 |
| Cut out (cm) | 19,5-21       |
| Weight (Kgr) | 0,186         |

### MATERIAL & COLOR

|                |         |
|----------------|---------|
| Product Color  | White   |
| Body Material  | Plastic |
| Cover Material | N/A     |

### APPLICATION & MOUNTING

|                            |                  |
|----------------------------|------------------|
| Ambient Working Temp.      | 45 C             |
| Type of Protection         | IP20             |
| Protection Class IK        | IK04             |
| Dimmable                   | No               |
| Type of Dimming (Optional) | N/A              |
| Mounting type              | Recessed/Surface |
| Mounting Depth (cm)        | Ceiling          |
| Led Module Replaceable     | No               |
| Light Source               | Led              |
| Adjustable                 | No               |

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com



# NOVA LUCE

## PRODUCT DATASHEET

Version: 001

### ELECTRICAL DATA

|                         |            |
|-------------------------|------------|
| Power (Nominal)         | 24         |
| Input voltage (Nominal) | 220-240Vac |
| Mains Frequency         | 50/60Hz    |
| Output voltage          | N/A        |
| Output Current          | N/A        |
| Power Factor            | 0,5        |
| Efficiency              | >73%       |
| SVM                     | 60.4       |
| Pst                     | 61         |
| Class                   | II         |

### PHOTOMETRICAL DATA

|                           |               |
|---------------------------|---------------|
| Luminus Flux              | 1940          |
| Luminous Efficacy         | 80.8          |
| Color Temperature         | 4000          |
| Light Color (Designation) | Neutral White |
| CRI                       | >80           |
| SDCM                      | <3            |
| Beam Angle                | 120           |
| UGR                       | N/A           |

### LIFESPAN

|          |       |
|----------|-------|
| Lifetime | 25000 |
|----------|-------|

### CERTIFICATES

|              |          |
|--------------|----------|
| Certificates | CE, UKCA |
|--------------|----------|

### WARRANTY

|          |         |
|----------|---------|
| Warranty | 2 Years |
|----------|---------|

### LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com

