

# NOVA LUCE

## PRODUCT DATASHEET

Version: 001

### PRODUCT PHOTOGRAPH




### GENERAL INFORMATION

|                         |                  |
|-------------------------|------------------|
| Product Code            | 9080801          |
| Product Category        | Industrial       |
| Product Family          | Dirpno           |
| Mounting Location       | Dampproof        |
| Application Environment | Indoor - Outdoor |

### DIMENSION & WEIGHT

|              |                 |
|--------------|-----------------|
| LxWxH (cm)   | L 120 W 4.8 H 6 |
| Cut out (cm) | -               |
| Weight (Kgr) | -               |

### TECHNICAL DRAWING



### MATERIAL & COLOR

|               |               |
|---------------|---------------|
| Product Color | White         |
| Body Material | Polycarbonate |
| Reflector     | -             |

### APPLICATION & MOUNTING

|                            |           |
|----------------------------|-----------|
| Ambient Working Temp.      | Max 40 oC |
| Type of Protection         | IP65      |
| Protection Class IK        | IK08      |
| Dimmable                   | No        |
| Type of Dimming (Optional) | N/A       |
| Mounting type              | N/A       |
| Mounting Depth (cm)        | N/A       |
| Led Module Replaceable     | No        |
| Light Source               | Led       |

### COMPATIBLE WITH

- On/Off Driver: Included
- Triac Driver:
- Dali Driver:

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com



# NOVA LUCE

## PRODUCT DATASHEET

Version: 001

### ELECTRICAL DATA

|                         |            |
|-------------------------|------------|
| Power (Nominal)         | 36W        |
| Input voltage (Nominal) | 220-240Vac |
| Mains Frequency         | 50/60Hz    |
| Output voltage          | 36Vdc      |
| Output Current          | N/A        |
| Power Factor            | N/A        |
| Efficiency              | N/A        |
| SVM                     | <0.4       |
| Pst                     | <1         |
| Class                   | I          |

### PHOTOMETRICAL DATA

|                                      |         |
|--------------------------------------|---------|
| Luminus Flux                         | 4820lm  |
| Luminous Efficacy (Complete Product) | 134lm/W |
| Color Temperature                    | 6500K   |
| Light Color (Designation)            | White   |
| CRI                                  | >80     |
| SDCM                                 | <3      |
| Beam Angle                           | 120°    |
| UGR                                  | N/A     |

### LIFESPAN

|          |       |
|----------|-------|
| Lifetime | 50000 |
|----------|-------|

### CERTIFICATES

|              |          |
|--------------|----------|
| Certificates | CE, UCKA |
|--------------|----------|

### WARRANTY

|          |         |
|----------|---------|
| Warranty | 5 years |
|----------|---------|

### LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com

