


PRODUCT PHOTOGRAPH



TECHNICAL DRAWING



COMPATIBLE WITH

— On/Off Driver: 9030472

— Triac Driver: 9844008(Remote)

— Dali Driver: 9621523 / 9844010

GENERAL INFORMATION

Product Code	9110121
Product Category	Downlights
Product Family	Glade
Mounting Location	Ceiling
Application Environment	Indoor

DIMENSION & WEIGHT

LxWxH (cm)	D:8.5 H:7.5
Cut out (cm)	4
Weight (Kgr)	N/A

MATERIAL & COLOR

Product Color	White
Body Material	Aluminium
Cover Material	N/A

APPLICATION & MOUNTING

Ambient Working Temp.	45 C
Type of Protection	IP20
Protection Class IK	IK05
Dimmable	Yes
Type of Dimming (Optional)	Triac/Dali
Mounting type	Trimless
Mounting Depth (cm)	Ceiling
Led Module Replaceable	No
Light Source	Led
Adjustable	No



NOVA LUCE

PRODUCT DATASHEET

Version: 001

ELECTRICAL DATA

Power (Nominal)	7
Input voltage (Nominal)	18Vdc
Mains Frequency	50/60Hz
Output voltage	18Vdc
Output Current	350mA
Power Factor	0.95
Efficiency	>80%
SVM	<0.4
Pst	<1
Class	III

PHOTOMETRICAL DATA

Luminus Flux	150
Luminous Efficacy	21.4
Color Temperature	2700
Light Color (Designation)	Warm White
CRI	97
SDCM	<3
Beam Angle	15
UGR	<7

LIFESPAN

Lifetime	50000
----------	--------------

CERTIFICATES

Certificates	CE, UKCA
--------------	-----------------

WARRANTY

Warranty	5 Years
----------	----------------

LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias
32009, Greece

+30 22620 58 121
+30 22620 56 743

info@novaluce.com
www.novaluce.com

