

# NOVA LUCE

## PRODUCT DATASHEET

Version: 001

### PRODUCT PHOTOGRAPH




### GENERAL INFORMATION

|                         |                 |
|-------------------------|-----------------|
| Product Code            | 9136753         |
| Product Category        | Facade & Accent |
| Product Family          | Dio             |
| Mounting Location       | Ceiling         |
| Application Environment | Outdoor         |

### DIMENSION & WEIGHT

|              |                       |
|--------------|-----------------------|
| LxWxH (cm)   | L:15.5 W:4.7 H:8.5 cm |
| Cut out (cm) | N/A                   |
| Weight (Kgr) | N/A                   |

### TECHNICAL DRAWING



### MATERIAL & COLOR

|                |           |
|----------------|-----------|
| Product Color  | White     |
| Body Material  | Aluminium |
| Cover Material | N/A       |

### APPLICATION & MOUNTING

|                            |             |
|----------------------------|-------------|
| Ambient Working Temp.      | 45 C        |
| Type of Protection         | IP65        |
| Protection Class IK        | IK07        |
| Dimmable                   | No          |
| Type of Dimming (Optional) | N/A         |
| Mounting type              | Surface     |
| Mounting Depth (cm)        | Ground/Wall |
| Led Module Replaceable     | No          |
| Light Source               | Led         |
| Adjustable                 | No          |

### COMPATIBLE WITH

- On/Off Driver: Included
- Triac Driver: N/A
- Dali Driver: N/A

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com



# NOVA LUCE

## PRODUCT DATASHEET

Version: 001

### ELECTRICAL DATA

|                         |            |
|-------------------------|------------|
| Power (Nominal)         | 4          |
| Input voltage (Nominal) | 220-240Vac |
| Mains Frequency         | 50/60Hz    |
| Output voltage          | N/A        |
| Output Current          | N/A        |
| Power Factor            | N/A        |
| Efficiency              | N/A        |
| SVM                     | N/A        |
| Pst                     | N/A        |
| Class                   | I          |

### PHOTOMETRICAL DATA

|                           |            |
|---------------------------|------------|
| Luminus Flux              | 60         |
| Luminous Efficacy         | 15         |
| Color Temperature         | 2700       |
| Light Color (Designation) | Warm White |
| CRI                       | >80        |
| SDCM                      | <3         |
| Beam Angle                | 20         |
| UGR                       | N/A        |

### LIFESPAN

|          |       |
|----------|-------|
| Lifetime | 50000 |
|----------|-------|

### CERTIFICATES

|              |          |
|--------------|----------|
| Certificates | CE, UKCA |
|--------------|----------|

### WARRANTY

|          |         |
|----------|---------|
| Warranty | 5 Years |
|----------|---------|

### LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com

