


PRODUCT PHOTOGRAPH



TECHNICAL DRAWING



COMPATIBLE WITH

— On/Off Driver: N/A

— Triac Driver: N/A

— Dali Driver: N/A

GENERAL INFORMATION

Product Code	9203121
Product Category	Faade & Accent Lighting
Product Family	Narrow
Mounting Location	Ground
Application Environment	Outdoor

DIMENSION & WEIGHT

LxWxH (cm)	D:18 H:18.7 cm
Cut out (cm)	17,5
Weight (Kgr)	N/A

MATERIAL & COLOR

Product Color	Silver
Body Material	Stainless Steel 316
Cover Material	N/A

APPLICATION & MOUNTING

Ambient Working Temp.	45 C
Type of Protection	IP67
Protection Class IK	IK08
Dimmable	N/A
Type of Dimming (Optional)	N/A
Mounting type	Surface
Mounting Depth (cm)	Ground
Led Module Replaceable	No
Light Source	Led
Adjustable	No



NOVA LUCE

PRODUCT DATASHEET

Version: 001

ELECTRICAL DATA

Power (Nominal)	14
Input voltage (Nominal)	110-240Vac
Mains Frequency	50/60Hz
Output voltage	N/A
Output Current	N/A
Power Factor	N/A
Efficiency	N/A
SVM	N/A
Pst	N/A
Class	I

PHOTOMETRICAL DATA

Luminus Flux	1232
Luminous Efficacy	88
Color Temperature	3000
Light Color (Designation)	Warm White
CRI	N/A
SDCM	<3
Beam Angle	38
UGR	N/A

LIFESPAN

Lifetime	50000
----------	-------

CERTIFICATES

Certificates	CE, UKCA
--------------	----------

WARRANTY

Warranty	5 Years
----------	---------

LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias
32009, Greece

+30 22620 58 121
+30 22620 56 743

info@novaluce.com
www.novaluce.com

