

PRODUCT PHOTOGRAPH



GENERAL INFORMATION

Product Code	9248067
Product Category	Downlights-Commercial
Product Family	Urby
Mounting Location	Ceiling
Application Environment	Indoor

DIMENSION & WEIGHT

LxWxH (cm)	D:12.9 H:5.6
Cut out (cm)	11
Weight (Kgr)	0,3

TECHNICAL DRAWING



MATERIAL & COLOR

Product Color	White
Body Material	Aluminium
Cover Material	N/A

APPLICATION & MOUNTING

Ambient Working Temp.	45 C
Type of Protection	IP20
Protection Class IK	IK03
Dimmable	Yes
Type of Dimming (Optional)	Triac/Dali
Mounting type	Recessed
Mounting Depth (cm)	Ceiling
Led Module Replaceable	No
Light Source	Led
Adjustable	No

COMPATIBLE WITH

- On/Off Driver:Included
- Triac Driver: 9844008
- Dali Driver: 9621523 / 9844010



NOVA LUCE

PRODUCT DATASHEET

Version: 001

ELECTRICAL DATA

Power (Nominal)	9
Input voltage (Nominal)	220-240Vac
Mains Frequency	50/60Hz
Output voltage	36Vdc
Output Current	250mA
Power Factor	0,9
Efficiency	>80%
SVM	<0.4
Pst	<1
Class	II

PHOTOMETRICAL DATA

Luminus Flux	640
Luminous Efficacy	71.1
Color Temperature	4000
Light Color (Designation)	Neutral White
CRI	>90
SDCM	<3
Beam Angle	120
UGR	<19

LIFESPAN

Lifetime	50000
----------	--------------

CERTIFICATES

Certificates	CE, UKCA
--------------	-----------------

WARRANTY

Warranty	5 Years
----------	----------------

LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias
32009, Greece

+30 22620 58 121
+30 22620 56 743

info@novaluce.com
www.novaluce.com

