

PRODUCT PHOTOGRAPH




GENERAL INFORMATION

Product Code	9248078
Product Category	Downlights
Product Family	Helio
Mounting Location	Ceiling
Application Environment	Indoor

DIMENSION & WEIGHT

LxWxH (cm)	L:16.7 W:8.5 H:6
Cut out (cm)	7,5*15,8
Weight (Kgr)	N/A

TECHNICAL DRAWING



MATERIAL & COLOR

Product Color	White
Body Material	Aluminium
Cover Material	N/A

APPLICATION & MOUNTING

Ambient Working Temp.	45 C
Type of Protection	IP20
Protection Class IK	IK03
Dimmable	Yes
Type of Dimming (Optional)	Triac/Dali
Mounting type	Recessed
Mounting Depth (cm)	Ceiling
Led Module Replaceable	No
Light Source	Led
Adjustable	No

COMPATIBLE WITH

- On/Off Driver: Included
- Triac Driver: 9844002
- Dali Driver: 9621521



NOVA LUCE

PRODUCT DATASHEET

Version: 001

ELECTRICAL DATA

Power (Nominal)	25
Input voltage (Nominal)	220-240Vac
Mains Frequency	50/60Hz
Output voltage	42Vdc
Output Current	600mA
Power Factor	0,9
Efficiency	>80%
SVM	<0.4
Pst	<1
Class	II

PHOTOMETRICAL DATA

Luminus Flux	1219
Luminous Efficacy	48.8
Color Temperature	3000
Light Color (Designation)	Warm White
CRI	>90
SDCM	<3
Beam Angle	36
UGR	<19

LIFESPAN

Lifetime	30000
----------	--------------

CERTIFICATES

Certificates	CE, UKCA
--------------	-----------------

WARRANTY

Warranty	3 Years
----------	----------------

LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias
32009, Greece

+30 22620 58 121
+30 22620 56 743

info@novaluce.com
www.novaluce.com

