

# NOVA LUCE

## PRODUCT DATASHEET

Version: 001

### PRODUCT PHOTOGRAPH



### TECHNICAL DRAWING



### COMPATIBLE WITH

- On/Off Driver: Included
- Triac Driver: N/A
- Dali Driver: N/A

### GENERAL INFORMATION

|                         |           |
|-------------------------|-----------|
| Product Code            | 9492912   |
| Product Category        | Systems   |
| Product Family          | Imagine 2 |
| Mounting Location       | Ceiling   |
| Application Environment | Indoor    |

### DIMENSION & WEIGHT

|              |              |
|--------------|--------------|
| LxWxH (cm)   | D:4 H:150 cm |
| Cut out (cm) | N/A          |
| Weight (Kgr) | 0,42         |

### MATERIAL & COLOR

|                |           |
|----------------|-----------|
| Product Color  | White     |
| Body Material  | Aluminium |
| Cover Material | N/A       |

### APPLICATION & MOUNTING

|                            |           |
|----------------------------|-----------|
| Ambient Working Temp.      | 45 C      |
| Type of Protection         | IP20      |
| Protection Class IK        | IK08      |
| Dimmable                   | No        |
| Type of Dimming (Optional) | N/A       |
| Mounting type              | Suspended |
| Mounting Depth (cm)        | Ceiling   |
| Led Module Replaceable     | No        |
| Light Source               | Led       |
| Adjustable                 | No        |

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com



# NOVA LUCE

## PRODUCT DATASHEET

Version: 001

### ELECTRICAL DATA

|                         |            |
|-------------------------|------------|
| Power (Nominal)         | 8          |
| Input voltage (Nominal) | 220-240Vac |
| Mains Frequency         | 50/60Hz    |
| Output voltage          | 36Vdc      |
| Output Current          | 180mA      |
| Power Factor            | 0.5        |
| Efficiency              | 87.3%      |
| SVM                     | 0,012      |
| Pst                     | 0,012      |
| Class                   | II         |

### PHOTOMETRICAL DATA

|                           |            |
|---------------------------|------------|
| Luminus Flux              | 565        |
| Luminous Efficacy         | 70.6       |
| Color Temperature         | 3000       |
| Light Color (Designation) | Warm White |
| CRI                       | >90        |
| SDCM                      | <3         |
| Beam Angle                | 24         |
| UGR                       | <16        |

### LIFESPAN

|          |       |
|----------|-------|
| Lifetime | 30000 |
|----------|-------|

### CERTIFICATES

|              |          |
|--------------|----------|
| Certificates | CE, UKCA |
|--------------|----------|

### WARRANTY

|          |         |
|----------|---------|
| Warranty | 5 Years |
|----------|---------|

### LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com

