

NOVA LUCE


PRODUCT DATASHEET

Version: 001

PRODUCT PHOTOGRAPH



TECHNICAL DRAWING



COMPATIBLE WITH

- On/Off Driver: Included
- Triac Driver: 9540320
- Dali Driver: 9621521

GENERAL INFORMATION

Product Code	9540305
Product Category	Downlights-Commercial
Product Family	Radius
Mounting Location	Ceiling
Application Environment	Indoor

DIMENSION & WEIGHT

LxWxH (cm)	D:19 H:12
Cut out (cm)	16,5
Weight (Kgr)	N/A

MATERIAL & COLOR

Product Color	White
Body Material	Aluminium
Cover Material	N/A

APPLICATION & MOUNTING

Ambient Working Temp.	45 C
Type of Protection	IP44
Protection Class IK	IK04
Dimmable	Yes
Type of Dimming (Optional)	Dali
Mounting type	Recessed
Mounting Depth (cm)	Ceiling
Led Module Replaceable	No
Light Source	Led
Adjustable	No

NOVA LUCE S.A

Schimatari Viotias
32009, Greece

+30 22620 58 121
+30 22620 56 743

info@novaluce.com
www.novaluce.com



NOVA LUCE

PRODUCT DATASHEET

Version: 001

ELECTRICAL DATA

Power (Nominal)	30
Input voltage (Nominal)	220-240Vac
Mains Frequency	50/60Hz
Output voltage	40Vdc
Output Current	800mA
Power Factor	0,9
Efficiency	86%
SVM	0.4
Pst	1
Class	II

PHOTOMETRICAL DATA

Luminus Flux	2918
Luminous Efficacy	97.3
Color Temperature	3000/4000/5700
Light Color (Designation)	Dip-Switch
CRI	>90
SDCM	<3
Beam Angle	60
UGR	<19

LIFESPAN

Lifetime	50000
----------	-------

CERTIFICATES

Certificates	CE ROHS
--------------	---------

WARRANTY

Warranty	5 Years
----------	---------

LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias
32009, Greece

+30 22620 58 121
+30 22620 56 743

info@novaluce.com
www.novaluce.com

