

PRODUCT PHOTOGRAPH




GENERAL INFORMATION

Product Code	9580655
Product Category	Low Voltage Tracks
Product Family	Ultra Thin
Mounting Location	Track
Application Environment	Indoor

DIMENSION & WEIGHT

LxWxH (cm)	:23.6 W:2.4 H:2.6 cm
Cut out (cm)	N/A
Weight (Kgr)	N/A

TECHNICAL DRAWING



MATERIAL & COLOR

Product Color	White
Body Material	Aluminium
Cover Material	N/A

APPLICATION & MOUNTING

Ambient Working Temp.	45 C
Type of Protection	IP20
Protection Class IK	IK04
Dimmable	Yes
Type of Dimming (Optional)	Triac
Mounting type	Surface
Mounting Depth (cm)	Track
Led Module Replaceable	N/A
Light Source	Led
Adjustable	Yes

COMPATIBLE WITH

- On/Off Driver: N/A
- Triac Driver: N/A
- Dali Driver: N/A



NOVA LUCE

PRODUCT DATASHEET

Version: 001

ELECTRICAL DATA

Power (Nominal)	12
Input voltage (Nominal)	24Vdc
Mains Frequency	50/60Hz
Output voltage	N/A
Output Current	N/A
Power Factor	N/A
Efficiency	N/A
SVM	N/A
Pst	N/A
Class	III

PHOTOMETRICAL DATA

Luminus Flux	673
Luminous Efficacy	56.1
Color Temperature	3000
Light Color (Designation)	Warm White
CRI	>90
SDCM	<3
Beam Angle	24
UGR	<19

LIFESPAN

Lifetime	50000
----------	-------

CERTIFICATES

Certificates	CE, UKCA
--------------	----------

WARRANTY

Warranty	5 Years
----------	---------

LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias
32009, Greece

+30 22620 58 121
+30 22620 56 743

info@novaluce.com
www.novaluce.com

