

PRODUCT PHOTOGRAPH



TECHNICAL DRAWING

COMPATIBLE WITH

- On/Off Driver: N/A
- Triac Driver: N/A
- Dali Driver: N/A

GENERAL INFORMATION

Product Code	9621505
Product Category	Accessories
Product Family	Drivers
Mounting Location	N/A
Application Environment	Outdoor

DIMENSION & WEIGHT

LxWxH (cm)	L: 18 W: 6,3 H: 3,55
Cut out (cm)	0
Weight (Kgr)	N/A

MATERIAL & COLOR

Product Color	N/A
Body Material	N/A
Cover Material	N/A

APPLICATION & MOUNTING

Ambient Working Temp.	45 C
Type of Protection	IP67
Protection Class IK	N/A
Dimmable	No
Type of Dimming (Optional)	N/A
Mounting type	N/A
Mounting Depth (cm)	N/A
Led Module Replaceable	N/A
Light Source	N/A
Adjustable	N/A



NOVA LUCE

PRODUCT DATASHEET

Version: 001

ELECTRICAL DATA

Power (Nominal)	100 W
Input voltage (Nominal)	100-240Vac
Mains Frequency	50/60Hz
Output voltage	48Vdc
Output Current	N/A
Power Factor	0.97
Efficiency	>90%
SVM	N/A
Pst	N/A
Class	N/A

PHOTOMETRICAL DATA

Luminus Flux	N/A
Luminous Efficacy	N/A
Color Temperature	N/A
Light Color (Designation)	N/A
CRI	N/A
SDCM	N/A
Beam Angle	N/A
UGR	N/A

LIFESPAN

Lifetime	50000 hours
----------	-------------

CERTIFICATES

Certificates	CE, ENEC, UKCA
--------------	----------------

WARRANTY

Warranty	5 years
----------	---------

LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias
32009, Greece

+30 22620 58 121
+30 22620 56 743

info@novaluce.com
www.novaluce.com

