

# NOVA LUCE


## PRODUCT DATASHEET

Version: 001

### PRODUCT PHOTOGRAPH



### TECHNICAL DRAWING



### COMPATIBLE WITH

- On/Off Driver: N/A
- Triac Driver: N/A
- Dali Driver: N/A

### GENERAL INFORMATION

|                         |              |
|-------------------------|--------------|
| Product Code            | 9680161      |
| Product Category        | Systems      |
| Product Family          | Glow         |
| Mounting Location       | Ceiling/Wall |
| Application Environment | Indoor       |

### DIMENSION & WEIGHT

|              |                   |
|--------------|-------------------|
| LxWxH (cm)   | L:4 W:4 H:20.3 cm |
| Cut out (cm) | N/A               |
| Weight (Kgr) | 0,27              |

### MATERIAL & COLOR

|                |           |
|----------------|-----------|
| Product Color  | Black     |
| Body Material  | Aluminium |
| Cover Material | N/A       |

### APPLICATION & MOUNTING

|                            |              |
|----------------------------|--------------|
| Ambient Working Temp.      | 45 C         |
| Type of Protection         | IP20         |
| Protection Class IK        | IK04         |
| Dimmable                   | No           |
| Type of Dimming (Optional) | N/A          |
| Mounting type              | Surface      |
| Mounting Depth (cm)        | Ceiling/Wall |
| Led Module Replaceable     | No           |
| Light Source               | Led          |
| Adjustable                 | No           |

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com



# NOVA LUCE

## PRODUCT DATASHEET

Version: 001

### ELECTRICAL DATA

|                         |         |
|-------------------------|---------|
| Power (Nominal)         | 6       |
| Input voltage (Nominal) | 24Vdc   |
| Mains Frequency         | 50/60Hz |
| Output voltage          | N/A     |
| Output Current          | N/A     |
| Power Factor            | N/A     |
| Efficiency              | N/A     |
| SVM                     | N/A     |
| Pst                     | N/A     |
| Class                   | III     |

### PHOTOMETRICAL DATA

|                           |            |
|---------------------------|------------|
| Luminus Flux              | 206        |
| Luminous Efficacy         | 34.3       |
| Color Temperature         | 3000       |
| Light Color (Designation) | Warm White |
| CRI                       | >90        |
| SDCM                      | <3         |
| Beam Angle                | 24         |
| UGR                       | <10        |

### LIFESPAN

|          |       |
|----------|-------|
| Lifetime | 30000 |
|----------|-------|

### CERTIFICATES

|              |          |
|--------------|----------|
| Certificates | CE, UKCA |
|--------------|----------|

### WARRANTY

|          |         |
|----------|---------|
| Warranty | 3 Years |
|----------|---------|

### LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com

