

PRODUCT PHOTOGRAPH




GENERAL INFORMATION

Product Code	9695189
Product Category	Downlights-Linear
Product Family	Eluvia
Mounting Location	Ceiling
Application Environment	Indoor

DIMENSION & WEIGHT

LxWxH (cm)	L:11.7 W:4.5 H:4.3
Cut out (cm)	11X3,6
Weight (Kgr)	N/A

TECHNICAL DRAWING



MATERIAL & COLOR

Product Color	White
Body Material	Aluminium
Cover Material	N/A

APPLICATION & MOUNTING

Ambient Working Temp.	45 C
Type of Protection	IP20
Protection Class IK	IK04
Dimmable	Yes
Type of Dimming (Optional)	Triac/Dali
Mounting type	Recessed
Mounting Depth (cm)	Ceiling
Led Module Replaceable	No
Light Source	Led
Adjustable	Yes

COMPATIBLE WITH

— On/Off Driver: Included

— Triac Driver: 9844008(Remote)

— Dali Driver: 9621523 / 9844010



NOVA LUCE

PRODUCT DATASHEET

Version: 001

ELECTRICAL DATA

Power (Nominal)	8
Input voltage (Nominal)	220-240Vac
Mains Frequency	50/60Hz
Output voltage	40Vdc
Output Current	200mA
Power Factor	0,5
Efficiency	>73%
SVM	60.4
Pst	61
Class	II

PHOTOMETRICAL DATA

Luminus Flux	401
Luminous Efficacy	50.1
Color Temperature	3000
Light Color (Designation)	Warm White
CRI	>90
SDCM	<3
Beam Angle	24
UGR	<12

LIFESPAN

Lifetime	50000
----------	-------

CERTIFICATES

Certificates	CE, UKCA
--------------	----------

WARRANTY

Warranty	5 Years
----------	---------

LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias
32009, Greece

+30 22620 58 121
+30 22620 56 743

info@novaluce.com
www.novaluce.com

