

# NOVA LUCE

## PRODUCT DATASHEET

Version: 001

### PRODUCT PHOTOGRAPH



### GENERAL INFORMATION

|                         |                    |
|-------------------------|--------------------|
| Product Code            | 9810090            |
| Product Category        | Low Voltage Tracks |
| Product Family          | Minimal            |
| Mounting Location       | Ceiling            |
| Application Environment | Indoor             |

### DIMENSION & WEIGHT

|              |                 |
|--------------|-----------------|
| LxWxH (cm)   | D:2.8 H:11.5 cm |
| Cut out (cm) | N/A             |
| Weight (Kgr) | N/A             |


### MATERIAL & COLOR

|                |           |
|----------------|-----------|
| Product Color  | Black     |
| Body Material  | Aluminium |
| Cover Material | N/A       |

### APPLICATION & MOUNTING

|                            |         |
|----------------------------|---------|
| Ambient Working Temp.      | 45 C    |
| Type of Protection         | IP20    |
| Protection Class IK        | IK03    |
| Dimmable                   | No      |
| Type of Dimming (Optional) | N/A     |
| Mounting type              | Track   |
| Mounting Depth (cm)        | Ceiling |
| Led Module Replaceable     | No      |
| Light Source               | Led     |
| Adjustable                 | Yes     |

### TECHNICAL DRAWING



### COMPATIBLE WITH

- On/Off Driver: N/A
- Triac Driver: N/A
- Dali Driver: N/A

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com



# NOVA LUCE

## PRODUCT DATASHEET

Version: 001

### ELECTRICAL DATA

|                         |         |
|-------------------------|---------|
| Power (Nominal)         | 6       |
| Input voltage (Nominal) | 48Vdc   |
| Mains Frequency         | 50/60Hz |
| Output voltage          | N/A     |
| Output Current          | N/A     |
| Power Factor            | N/A     |
| Efficiency              | N/A     |
| SVM                     | N/A     |
| Pst                     | N/A     |
| Class                   | III     |

### PHOTOMETRICAL DATA

|                           |            |
|---------------------------|------------|
| Luminus Flux              | 116        |
| Luminous Efficacy         | 19.3       |
| Color Temperature         | 3000       |
| Light Color (Designation) | Warm White |
| CRI                       | 95         |
| SDCM                      | <3         |
| Beam Angle                | 20-33      |
| UGR                       | <19        |

### LIFESPAN

|          |       |
|----------|-------|
| Lifetime | 50000 |
|----------|-------|

### CERTIFICATES

|              |          |
|--------------|----------|
| Certificates | CE, UKCA |
|--------------|----------|

### WARRANTY

|          |         |
|----------|---------|
| Warranty | 5 Years |
|----------|---------|

### LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com

