

NOVA LUCE


PRODUCT DATASHEET

Version: 001

PRODUCT PHOTOGRAPH



TECHNICAL DRAWING



COMPATIBLE WITH

- On/Off Driver: included
- Triac Driver: 9844008 (remote)
- Dali Driver: 9844146

GENERAL INFORMATION

Product Code	9844023
Product Category	Spot
Product Family	Glyce
Mounting Location	Ceiling
Application Environment	Indoor

DIMENSION & WEIGHT

LxWxH (cm)	D: 4 H: 6
Cut out (cm)	D: 3.5
Weight (Kgr)	-

MATERIAL & COLOR

Product Color	Black
Body Material	Aluminium
Cover Material	N/A

APPLICATION & MOUNTING

Ambient Working Temp.	Max 40 oC
Type of Protection	IP20
Protection Class IK	IK03
Dimmable	No
Type of Dimming (Optional)	N/A
Mounting type	Recessed
Mounting Depth (cm)	6
Led Module Replaceable	No
Light Source	Led

NOVA LUCE S.A

Schimatari Viotias
32009, Greece

+30 22620 58 121
+30 22620 56 743

info@novaluce.com
www.novaluce.com



NOVA LUCE

PRODUCT DATASHEET

Version: 001

ELECTRICAL DATA

Power (Nominal)	6W
Input voltage (Nominal)	220-240Vac
Output voltage	18Vdc
Output Current	300mA
Power Factor	0.5
Efficiency	>76%
SVM	<0.4
Pst	<1
Class	II

PHOTOMETRICAL DATA

Luminus Flux	378lm
Luminous Efficacy	63lm/W
Color Temperature	3000K
Light Color (Designation)	Warm White
CRI	90
SDCM	<4
Beam Angle	36°
UGR	<19

LIFESPAN

Lifetime	50000
----------	--------------

CERTIFICATES

Certificates	CE
--------------	-----------

WARRANTY

Warranty	5 years
----------	----------------

