

PRODUCT PHOTOGRAPH




GENERAL INFORMATION

Product Code	9844093
Product Category	Downlights-Linear
Product Family	Canon
Mounting Location	Ceiling
Application Environment	Indoor

DIMENSION & WEIGHT

LxWxH (cm)	L:21 W:4.4 H:4
Cut out (cm)	21,1 X 4
Weight (Kgr)	N/A

TECHNICAL DRAWING



MATERIAL & COLOR

Product Color	White
Body Material	Aluminium
Cover Material	N/A

APPLICATION & MOUNTING

Ambient Working Temp.	45 C
Type of Protection	IP20
Protection Class IK	IK04
Dimmable	Yes
Type of Dimming (Optional)	Triac/Dali
Mounting type	Recessed
Mounting Depth (cm)	Ceiling
Led Module Replaceable	No
Light Source	Led
Adjustable	No

COMPATIBLE WITH

— On/Off Driver: Included

— Triac Driver: 9844002(Remote)

— Dali Driver: 9621523



NOVA LUCE

PRODUCT DATASHEET

Version: 001

ELECTRICAL DATA

Power (Nominal)	15
Input voltage (Nominal)	220-240Vac
Mains Frequency	50/60Hz
Output voltage	30Vdc
Output Current	450mA
Power Factor	>0.82
Efficiency	ø86%
SVM	60.4
Pst	61
Class	II

PHOTOMETRICAL DATA

Luminus Flux	818
Luminous Efficacy	54.5
Color Temperature	3000
Light Color (Designation)	Warm White
CRI	>90
SDCM	<3
Beam Angle	28
UGR	<19

LIFESPAN

Lifetime	50000
----------	-------

CERTIFICATES

Certificates	CE, UKCA
--------------	----------

WARRANTY

Warranty	5 Years
----------	---------

LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias
32009, Greece

+30 22620 58 121
+30 22620 56 743

info@novaluce.com
www.novaluce.com

